AUCom MOTOR CONTROL SPECIALISTS

FOOD & BEVERAGE APPLICATIONS

BENEFIT		FEATURE	AUGER	BLOWER/ FAN	CENTRIFUGE	COMPRESSOR	MILL, ROLLER	MIXER	PELLETISER	PUMP	SEPARATOR	SLICER	STIRRER
Protect equipment	Prevent damage due to reverse operation	Phase sequence											
	Prevent damage from jammed loads	Instantaneous overcurrent											
	Early warning of abnormal load conditions to detect broken couplings, blocked pipes etc	Undercurrent								•			1
Maximise productivity	Safely use full motor capacity without nuisance tripping	_ Motor thermal model									(1000	
	Accurate motor protection during extended start								T				
	Ride through operating overloads eg large bones or frozen goods	Overcurrent + delay											
	Complete critical processes	PowerThrough											
	Control compressor loading according to motor loading	— Analog output							-	ap I I	77	A	
	Control infeed conveyor speed based on motor loading										SA.		
Smoother operation	Minimise stress on electrical supply	Reduced start current										T.	•
	Reduce mechanical stress during start	Gentle acceleration											•
Intelligent control of the whole system	Simplify control circuits by directly connecting external switches	Digital inputs									-400		17
	Override motor and system protections in emergency situations, eg fire pumps, ventilation fans	Emergency run											
	Improve system performance with closed loop process control	Analog output											